HARMO Robot Parts

Parallel Gripper

Characteristics

- The Parallel Lever Gripper has realized both compact size and large gripping power by applying a compact elliptic cylinder.
- Lightweight plastic type and durable die-cast alloy type are available.
- As for e sensor equipped type, the jaw operation and the clamping condition can be simply checked by the LED which goes on and off. The proximity switch can be moved in the lateral direction. By adjusting the location of the proximity switch according to the work pieces, the work piece's clamping condition can be checked.


Specifications

Series		HP15P	HP20P	HP20D	HP30D	
Actuating method		Double acting type				
Fluid medium		Compressed air (oilless)				
Operating pressure range		43 ~ 102psi (0.3 ~ 0.7MPa) 36.3 ~ 131psi		(0.25 ~ 0.9 MPa)		
Operating temp. range		14 ~ 140°F (-10 ~ 60°C) (no freezing)				
Port size		M5×0.8 mm				
Cylinder sectional area		1.7cm ²	3.3 cm ²		7.2cm ²	
Repeated accuracy		±0.05mm (at the center of the jaws)				
Cycle per minute		100C.P.M				
With brace	cket (B)	0	0	-	-	
With Ser	nsor (S)	0	0	0	0	

Sensor Specification

Power voltage	12 ~ 24VDC	
Power consumption	Max. 15 mA	
	NPN transistor open collector	
Output	Max. current: 100mA	
	Applied voltage: 30VDC max.	
Operation indicator lamp	Red LED (Lights when turned on)	
Ambient	14 ~ 131°F (-10 ~ +55°C)	
Cable	0.08SQ 3 cores, 1m	

Construction



	No	Parts	Material
1	(1)	Cam b	POM
⊳(5)	(2)	Cam a	POM
(3)	(3)	Piston	POM
	(4)	Cylinder	polyamide resin or zinc die casting
	(5)	Piston packing	NBR
i '	(6)	Rod packing	NBR
)	(7)	Slider	phosphor bronze
	(8)	Jaw	chromium-molybdenum steel

Detailed Safety Instructions

- 1. Use clear and dry air as supply air to Gripper.
- By grabbing as softly as possible, Gripper works accurately and repeat accuracy is stable.
- By grabbing as sorry as possible, chipper works according to sorry accord
- 4. Use lightest and shortest possible finger tool attached to jaws part.

Model Designation (Example)



(1) Cylinder area


ı	Code	15	20	30
/	Cylinder area	2.1cm ²	4.3cm ²	8.8cm ²

(2) Body material


Code (material)	P	D
Farallel Type Gripper Cade	(plastic)	(die cast)
HP15	0	-
HP20	0	0
HP30	_	0
HP30	-	0

(3) Option


(3) Optioi	n		
Code	-В	-S	No code
Panaled Type Gripper Cade	(with bracket)	(with sensor (with bracket))	(without option)
HP15P	0	0	\sim
HP20P	0	0	
HP20D	-	0	
HP30D	-	0	








HP	Model code
Vith Sensor	HP15P-S
	HP20P-S
2001	HP20D-S
- TO	HP30D-S
10000	



١v

Caution
* Make-to-order production



Option Parts

Model code of Sensor Set (*1)			Model code of Sensor only (*1)			
Model code	Gripper type	Note	Model code	Gripper type	Note	
D1002	HP15P	Set Item	D000907	All types	Sensor 1 pc. + Fixing Screw 1 pc.	
D1102	HP20P	Sensor, Sensor Fixing Screw, Limit				
D1112	HP20D	Dog, Dog Fixing Screw, Sensor	Model code of	ode of Limit Dog Fixing Screw for Sensor		
D1202	HP30D	Bracket, Sensor Bracket Fixing Screw	Model code	Gripper type	Note	
			/100613	HP15P		
Model code of	Model code of Limit Dog for Sensor (Dog only)			HP20P		
Model code	Gripper type	Note	/100813	HP20D	For fixing, 2 pcs. required.	
D100903	HP15P		/101015	HP30D		
D110903	HP20P	Des estu				
D111903	HP20D	Dog only	Model code of	f Sensor Bracket Attaching Screw		
D120903	HP30D		Model code	Gripper type	Note	
			/110010	HP15P	For fining 4 page required	
Model code of Sensor Bracket only			/110613	HP20P	For fixing, 4 pcs. required.	
Model code	Gripper type	Note	/000304	HP20D	For fixing, 2 pcs. required.	
D100902	HP15P		/000505	HP30D	For fixing, 4 pcs. required.	
		1				

D100902 HP15P D110902 HP20P Bracket with sensor mount D111902 HP20D only D120902 HP30D only

/000304 HP20D P011Xing, 2 /000505 HP30D For fixing, 4

Model code of Fixing Bracket only (not a sensor mount type) (*2)

Model code	Gripper type	Note
D100901	HP15P	Fixing Screw Size: M3×0.5
D110901	HP20P	Depth 5mm, 4 holes
		alter a construction of the construction of th

Caution

*1. The sensor is NPN Open collector output.
*2. No screw is included. Prepare Attaching Screw by yourself.

Package specifications 1 pc. in a bag: Limit Dog Fixing

1 pc. in a bag: Limit Dog Fixing Screw for Sensor Limit Dog for Sensor (Dog only) Sensor Bracket only Sensor Bracket Fixing Screw Bracket only (not a sensor mount type) 1 set ∠ bag: Sensor Set

Sensor only